

# **Automatic**

# **Screw Feeder**



Radial Indexing Escaper was installed in NSB & NSR model.

# NSRI

NEW



For Automatic Robot

# NSRI OPERATION OPERATION

Because escaper rotates slowly, the screw rarely jump out. The supply speed become quickly


The Suppry	speed become	quickiy.
Modeł Name	NSBI	NSR

	-	-
Size(mm)	123(W) × 181(D) × 145(H)mm	123(W) × 181(D) × 145(H)mm
Weight(including rail)	2. 94Kg	2.89Kg
Power Source	In:AC100~240V Out:E	OC15V 1A AC adapter
Protection &	Motor overload stop,	
Recovery Circuit	Protection circuit for reverse power connection	
Applicable Screw	From M1. 0 to M3. 0 (to	the table for applicable rails)
Applicable Screw	Up to 20mm	
Length(under head)		
Scooping Camber	80cc	
Capacity		

### Feature

Because of separating one screw, screws are hard to pile.

The screw on pick out section doesn't vibrate, so pulling out mistake can be prevented.



## Radial Indexing Escaper



Kompania Narzędziowa "HERMES" Sp. z o.o. ul. Sarni Stok 73 a, 43-300 Bielsko-Biała, Polska; tel: +48 33 821 41 90-91

e-mail: biuro@hermestools.eu

www.hermestools.eu