

Cordless riveter revolutionizes work sites

R2B2

● Specifications

Model No.	R2B2
Riveting cycle time ※1	1.3sec
Product weight (kg) ※2	2.3
Stroke (mm)	25
Overall length×Overall width×Overall height (mm) ※2	330×76×277
Frame head diameter (mm)	23
Minimum corner work distance (mm)	34
Motor specification	18V brushless
Maximum output (kN)	19.6
User range	4.8, 6.4 Full material
Jaw	Ultra-hard jaw



● Package item

Model No.	R2B2
Package item ※3	riveter, battery pack(BPL1825:18V/2.5Ah), charger, power cord for charger, lubricating oil, dedicated blow case Active grip nose piece unit (4.8, 6.4), guide pipe unit(4.8,6.4) spanner(19mm), ball screw joint collar(4.8,6.4)
Product weight (kg)	4.7
Case size (mm)	450×370×120
Retail/User prices	open price



● Battery pack specifications

Model No.	BPL1825 BPL1825KC	BPL1850 BPL1850KC
Type	Li-ion	Li-ion
Rated voltage (V)	18	18
Capacity (Ah)	5.0	5.0
Charging time ※4 (Charge for practical use / Full charging)	60 Minute / 65 Minute	125 Minute / 135 Minute
Retail/User prices	open price	open price

● Charger specifications

Model No.	BC037T	BC037T-120V	BC037T-230V	BC037T-KC
Power	AC100V	AC120V	AC230V	AC220V
Retail/User prices	open price			

